



DIT

Rugged door interlocking terminals, designed to maintain positive air pressure in a designated area.

HARDWARE

CPU	40 bit microcontroller running at 8 MHz
Program Memory	32 Kbytes
Communication	USB
Door Interface	2 Switch & 2 DOTL per door
Door Control	1 Buzzer & 2 LED indicators per door
Relay Interface	Relay outputs for lock : 3A @12V DC
Digital Inputs	4 general purpose optically isolated digital inputs
Digital Output	2 general purpose relay outputs
Watchdog	Inbuilt watchdog supervisor
Power	Less than 5 wattt
Operating Temp.	-10 to 50°C

DIT 800

Controller	8 Doors/16 Switches
Supply	Input :230V AC, Output : 13.8V DC/2.5 Amp with battery charger, provision to connect 12V/7.2 AH battery
Power	Less than 5 watt
Protection	Miniature circuit breaker (MCB) for over current protection
Weight	5.14Kg.
Dimensions	H 362 x W 325 x D 83

DIT 400

Controller	4 Doors/8 Switches
Supply	Input :230V AC, Output : 13.8V DC/2.5 Amp with battery charger, provision to connect 12V/7.2 AH battery
Power	Less than 5 watt
Protection	Miniature circuit breaker (MCB) for over current protection
Weight	2.65Kg.
Dimensions	H 262 x W 230 x D 57t

DIT 200

Controller	2 Doors/4 Switches
Supply	Input :230V AC, Output : 13.8V DC/2.5 Amp with battery charger, provision to connect 12V/7.2 AH battery
Power	Less than 5 watt
Protection	Miniature circuit breaker (MCB) for over current protection
Weight	2.65Kg.
Dimensions	H 262 x W 230 x D 57

Technical specifications may be changed from time to time without any prior notice due to continuous enhancements in the product.



Head Office

Spectra Technovision (India) Pvt. Ltd.
707-708-709, Venus Atlantis Corporate Park,
Prahlanadnagar, Ahmedabad-380015 India.

+91 79 44111222 ✉ sales@spectra-vision.com

Branch Offices

Mumbai ☎ +91 22 44111222

Bangalore ☎ +91 80 44111222

